



#### Technical Information

Video Amplifier Bandwidth: 165 MHz per channel  
Single Link Range: 1080p (HDTV) / 1920x1200 (PC)  
Input Video Signal: 1.2 Volts p-p  
Input DDC Signal: 5 Volts p-p (TTL)  
Remote Control Ports: One RS232 female, One mini-stereo  
Rack mountable: 2U rack space, rack ears included  
DVI Connector: DVI-I 29 Pin Female (digital only)  
Power Supply: 24V DC  
Power Consumption: 60 Watts (max)

#### Product Information

- Increases your productivity by providing you with access from eight workstations to eight computers
- Maintains beautiful, sharp HDTV resolutions up to 1080p, 2K, and 1920x1200
- Discrete IR remote control included
- Long-distance remote control at distances of up to 330 feet using optional by using wired CAT5 cabled remotes
- Serial RS232 port for remote control via computer or a control automation device such as Crestron
- Supports DDWG standards for DVI monitors.

**Disclaimer:** Changes in the data may have been made by the manufacturer without notice.

Centas Konferens-TV AB  
www.centas.se  
info@centas.se

Stockholm  
+46 8 724 04 00  
stockholm@centas.se

Malmö  
+46 40 14 38 00  
malmo@centas.se

Göteborg  
+46 31 84 01 00  
goteborg@centas.se