



Product Information

Tripod

A two stage, lightweight, high tensile aluminum tripod that is extremely rigid and stable. The 525MVB has a die-cast aluminum crown with a built-in 75mm interface bowl, adjustable leg clamp levers for reliability and safety in the field and a floor-level spreader which aids tripod leg angle setting adjustment. Lowest leg section has twin spiked metal feet. The tripod can also be equipped with spiked foot shoes, different types of dollies and two models of mid level spreader.

Technical Information

Closed length 72.0 cm 28.35 in
 Colour black color black color
 Head bowl 75mm 75mm
 Leg cross section round round
 Leg sections 3 number 3 number
 Legs tube diameter 16. 25mm
 Load capacity 15 kg
 Material aluminum aluminum
 Maximum height 156.0 cm
 Minimum height 36.0 cm
 Spreader low level - variable arm length low level - variable arm length
 Weight 3.5 kg

Product Information

Fluid Video Head

The 503HDV has a completely new ergonomic, easy-to-use, functional design; features include large ergonomic locks and knobs allowing for a more solid grip and better control. For enhanced ease of use, the tilt lock and friction controls are located on the left side of the head. It has an improved and adjustable counterbalance capacity: a switch controls the different counterbalance settings, allowing the user to adjust the system to accommodate various payloads for different filming needs. The counterbalance system can be adjusted to four positions ensuring both smoother tilt movements and greater equipment safety. In addition, it has an illuminated levelling bubble - making it easy for shooters to level the camera in low-light conditions. In addition to the old 503, the 503HDV has also a replaceable pan bar rosette

Technical Information

Tripod attachment type female thread to mount on 75 mm flat top tripod attachment type
 Balance control 4 step: 0Kg - 1.3Kg - 2.6Kg - 3.9Kg 4 step: 0Kg - 1.3Kg - 2.6Kg - 3.9Kg
 Front tilt -60° / +90° tilt range -60° / +90° tilt range
 Independent pan & tilt lock
 Levelling bubble illuminated illuminated
 Load capacity 8 kg 17.64 lbs
 Maximum /minimum working temperature 60/-20
 Pan bar positions 2 number /1 pan bars included
 Pan drag continuously adjustable from 0 to max level
 Panoramic rotation 360
 Plate type 501PL / quick release
 Weight 1.95 kg
 Working height 11.5 cm

Disclaimer: Changes in the data may have been made by the manufacturer without notice.

Centas Konferens-TV AB
 www.centas.se
 info@centas.se

Stockholm
 +46 8 724 04 00
 stockholm@centas.se

Malmö
 +46 40 14 38 00
 malmo@centas.se

Göteborg
 +46 31 84 01 00
 goteborg@centas.se